

Equipment Specifications

| Prime Power Rating | |
|--------------------------------|----------|
| 180 kVA (144 kW) | |
| Voltage Selectable | |
| AMPS @ 240V - 1PH, 1.0PF, 60Hz | N/A |
| AMPS @ 208V - 3PH, 0.8PF, 60Hz | 500 AMPS |
| AMPS @ 208V - 3PH, 1.0PF, 60Hz | 400 AMPS |
| AMPS @ 240V - 3PH, 0.8PF, 60Hz | 433 AMPS |
| AMPS @ 240V - 3PH, 1.0PF, 60Hz | 346 AMPS |
| AMPS @ 480V - 3PH, 0.8PF, 60Hz | 216 AMPS |
| AMPS @ 480V - 3PH, 1.0PF, 60Hz | 172 AMPS |

| Specs & Features | |
|---|-----------------|
| Dimensions (LxWxH) | 17' x 7' x 7'2" |
| Total Weight (lbs) | 9,600 lbs |
| Hitch Type | Pintle |
| Fuel Type | Diesel |
| Fuel Tank Capacity | 279 Gallons |
| Estimated Fuel Supply Hours @ 100% Load | 30 Hours |
| Estimated Fuel Supply Hours @ 50% Load | 59 Hours |

| Available Options for Select Models | |
|-------------------------------------|--|
| Auto-Start | |
| Remote Monitoring | |

Equipment specifications and available options may vary.